HIMOINSA
A YANMAR COMPANY

HSY-10 T5

HS | STATIONARY RANGE
Powered by YANMAR



SERVICE		PRP	ESP
POWER	kVA	8,3	8,9
POWER	kW	6,7	7,2
RATED SPEED	r.p.m.	1.500	
MAIN VOLTAGE	V	400/230	
AVAILABLE VOLTAGES	V	230/115 · 230 V (t) · 380/220 · 415/240	
RATED AT POWER FACTOR	Cos Phi	0,8	

HS | STATIONARY RANGE

HIMOINSA Company with quality certification ISO 9001

HIMOINSA gensets are compliant with EC mark which includes the following directives:

- 2006/42/CE Machinery safety.
- 2014/30/UE Electromagnetic compatibility.
- 2014/35/UE electrical equipment designed for use within certain voltage limits
- 2000/14/EC Sound Power level. Noise emissions outdoor equipment. (amended by 2005/88/EC)
- (UE) Nº 2016/1628 Emissions of gaseous and particulate pollutants
- EN 12100, EN 13857, EN 60204

Ambient conditions of reference according to ISO 8528-1:2018 normative: 1000 mbar, 25ºC, 30% relative humidity.

Prime Power (PRP):
According to ISO 8528-1:2018, Prime power is the maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load when operated for an unlimited number of hours per year under the agreed operating conditions with the maintenance intervals and procedures being carried out as prescribed by the manufacturer. The permissible average power output (Ppp) over 24 h of operation shall not exceed 70 % of the PRP.

Emergency Standby Power (ESP):
According to ISO 8528-1:2018, Emergency standby power is the maximum power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage or under test conditions for up to 200 h of operation per year with the maintenance intervals and procedures being carried out as prescribed by the manufacturers. The permissible average power output over 24 h of operation shall not exceed 70 % of the ESP

Continuous Power (COP): According to Standard ISO 8528-1:2018, this is the maximum power available for continuous loads for unlimited running hours a year between the maintenance times recommended by the manufacturer under the environmental conditions established by the same.

G2 class load acceptance in accordance with ISO 8528-5:2018

HIMOINSA HEADQUARTERS:
Fábrica: Ctra. Murcia - San Javier, Km. 23,6 | 30730 SAN JAVIER (Murcia) Spain
Tel.+34 968 19 11 28 Fax +34 968 19 12 17 Fax +34 968 19 04 20 | info@himoinsa.com | www.himoinsa.com

Manufacture facilities:
SPAIN • FRANCE • INDIA • CHINA • USA • BRAZIL • ARGENTINA

Subsidiaries:
PORTUGAL | POLAND | GERMANY | UK | SINGAPORE | UAE | PANAMA | DOMINICAN REPUBLIC | ARGENTINA | ANGOLA | SOUTH AFRICA

STANDARD SOUNDPROOFING

- HS10
- WATER-COOLED
- THREE PHASE
- 50 HZ
- STAGE V
- DIESEL

Himoinsa has the right to modify any feature without prior notice.

Weights and dimensions based on standard products. Illustrations may include optional equipment.

Technical data described in this catalogue correspond to the available information at the moment of printing.

The illustrations and images are indicative and may not coincide in their entirety with the product.

Industrial design under patent.

Engine Specifications | 1.500 r.p.m.

Rated Engine Output (PRP)	kW	8,2
Rated Engine Output (ESP)	kW	9
Manufacturer		YANMAR
Model		3TNV80FNGGEH
Engine Type		4-stroke diesel
Injection Type		Indirect
Aspiration Type		Natural
Number of cylinders and arrangement		3-L
Bore and Stroke	mm	80 x 84
Displacement	L	1,27
Cooling System		Liquid (water + 50% glycol)
Lube Oil Specifications		SAE 3 class 10W30 / API grade CD,CF
Compression Ratio		23,1

Total oil capacity	L	3,4
Total coolant capacity	L	4,4
Governor	Type	Mechanical
Air Filter	Type	Dry

- Diesel engine
- 4-stroke cycle
- Water-cooled
- 12V electrical system
- Dry air filter
- Radiator with pusher fan
- Mechanical governor
- Hot parts protection
- Moving parts protection

Generator Specifications | STAMFORD

Manufacturer		STAMFORD
Model		S0L1.H1
Poles	No.	4
Connection type (standard)		Star-series
Mounting type		S-5 7"1/2
Insulation	Class	H class

Enclosure (according IEC-34-5)	IP23
Exciter system	Self-excited, brushless
Voltage regulator	A.V.R. (Electronic)
Bracket type	Single bearing
Coupling system	Flexible disc
Coating type	Standard (Vacuum impregnation)

- Self-excited and self-regulated
- IP23 protection
- H class insulation

ISO 9001
Ctra. Murcia - San Javier, km. 23,6 | 30730 San Javier (Murcia) SPAIN | Tel.: +34 902 19 11 28 / +34 968 19 11 28
Fax: +34 968 19 12 17 | Export Fax +34 968 19 04 20 | E-mail:info@himoinsa.com | www.himoinsa.com
HIMOINSA
A YANMAR COMPANY

WEIGHT AND DIMENSIONS

		Standard Version	Optional version	Optional version	Optional version	Optional version	Optional version
Length (L)	mm	1.725	1.725	1.725	1.725	1.725	1.725
Height (H)	mm	1.270	1.120	1.320	1.370	1.420	1.620
Width (W)	mm	750	750	750	750	750	750
Maximum shipping volume	m^3	1,64	1,45	1,71	1,77	1,84	2,1
Weight with liquids in radiator and sump	Kg	526	Ask	Ask	Ask	Ask	Ask
Fuel tank capacity	L	100	Ask	140	180	225	385
Autonomy (100% PRP)	Hours	37	Ask	52	67	84	144
		Steel tank	Steel tank	Steel tank	Steel tank	Steel tank	Steel tank

SOUND PRESSURE

Sound pressure level	dB(A)@7m	60 ± 2,4
Sound pressure level with attenuation system	dB(A)@7m	56 ± 2,4

APPLICATION DATA

EXHAUST SYSTEM

Maximum exhaust temperature	°C	400
Exhaust Gas Flow	m^3/min	2,4
Maximum allowed back pressure	mm H2o	1000

NECESSARY AMOUNT OF AIR

Intake air flow	m^3/h	51,44
Cooling Air Flow	m^3/s	0,693
Alternator fan air flow	m^3/s	0,058

FUEL CONSUMPTION

Fuel Consumption ESP	l/h	2,82
Fuel Consumption 100% PRP	l/h	2,68
Fuel Consumption 70 % PRP	l/h	2,27

FUEL SYSTEM

Fuel Oil Specifications		Diesel
Fuel Tank	L	100
Other fuel tank capacities	L	140, 180, 225, 385

STARTING SYSTEM

Starting power	kW	1,1
Starting power	CV	1,5
Auxiliary Voltage	Vdc	12

Soundproofed version

- Steel chassis
- Lower power cable outlet with aluminum cover
- Side auxiliary cable outlet with aluminum cover
- Modular tank and retention tray system. Allows easy removal and / or maintenance of the equipment
- Wide access to the engine compartment because of a removable door
- Fuel tank in retention tray
- Soundproofing with foam and polyurethane film
- 4 side lifting points
- Anti-vibration shock absorbers
- Fuel tank
- Fuel level gauge
- External emergency stop switch
- Bodywork made from high quality steel plate
- High mechanical strength
- Epoxy polyester powder coating
- Full access for maintenance (water, oil and filters, no need to remove the canopy)
- Versatility to assemble a high capacity chassis with a metallic fuel tank
- IP Protection according to ISO 8528-13:2016
- Manual oil extraction pump (Opcional).
- Noise reduction kit (Opcional).
- Retention Tray (Opcional).
- Manual oil drain pump (Opcional).
- Fuel transfer pump (Opcional).



FEATURES OF THE CONTROL UNITS

		M7X	CEM 7	CEA 7	CEC 7	M7X+CEC7
Generator Readings	Voltage between phases	•	•	•	•	•
	Voltage between neutral and phase	•	•	•	•	•
	Current intensities	•	•	•	•	•
	Frequency	•	•	•	•	•
	Apparent power (Kva)	•	•	•	•	•
	Active power (Kw)	•	•	•	•	•
	Reactive power (kVAr)	•	•	•	•	•
	Power factor	•	•	•	•	•
Mains Readings	Voltage between phases			•	•	•
	Voltage between phases and neutral			•	•	•
	Current intensities			•	•	•
	Frequency			•	•	•
	Apparent power			•		
	Active power			•		
	Reactive power			•		
	Power factor			•		
Engine Readings	Coolant temperature	•	•	•		•
	Oil pressure	•	•	•		•
	Fuel level (%)	•	•	•		•
	Battery voltage	•	•	•		•
	R.P.M.	•	•	•		•
	Battery charge alternator voltage	•	•	•		•
Engine Protections	High water temperature	•	•	•		•
	High water temperature by sensor	•	•	•		•
	Low water temperature by sensor	•	•	•		•
	Low oil pressure	•	•	•		•
	Low oil pressure by sensor	•	•	•		•
	Low water level	•	•	•		•
	Unexpected shutdown	•	•	•		•
	Fuel storage	•	•	•		•
	Fuel storage by sensor	•	•	•		•
	Stop failure	•	•	•		•
	Battery voltage failure	•	•	•		•
	Battery charge alternator failure	•	•	•		•
	Overspeed	•	•	•		•
	Underspeed	•	•	•		•
	Start failure	•	•	•		•
	Emergency stop	•	•	•	•	•

• Standard ⓞ Optional

2023-JUN.-02 10:59

		M7X	CEM 7	CEA 7	CEC 7	M7X+CEC7
Alternator Protections	High frequency	●	●	●	●	●
	Low frequency	●	●	●	●	●
	High voltage	●	●	●	●	●
	Low voltage	●	●	●	●	●
	Short-circuit	●	●	●		●
	Asymmetry between phases	●	●	●	●	●
	Incorrect phase sequence	●	●	●	●	●
	Inverse power	●	●	●		●
	Overload	●	●	●		●
	Genset signal drop	●	●	●	●	●
Counters	Total hour counter	●	●	●	●	●
	Partial hour counter	●	●	●	●	●
	Kilowatt meter	●	●	●	●	●
	Starts valid counters	●	●	●	●	●
	Starts failure counters	●	●	●	●	●
	Maintenance	●	●	●	●	●
Communications	RS232		ⓞ	ⓞ	ⓞ	ⓞ
	RS485		ⓞ	ⓞ	ⓞ	ⓞ
	Modbus IP		ⓞ	ⓞ	ⓞ	ⓞ
	Modbus		ⓞ	ⓞ	ⓞ	ⓞ
	CCLAN		ⓞ	ⓞ		
	Software for PC		ⓞ	ⓞ	ⓞ	ⓞ
	Analogue modem		ⓞ	ⓞ	ⓞ	ⓞ
	GSM/GPRS modem		ⓞ	ⓞ	ⓞ	ⓞ
	Remote screen		ⓞ	ⓞ		
	Tele signal		ⓞ (8 + 4)	ⓞ (8 + 4)		
	J1939	ⓞ M7XJ	ⓞ	ⓞ		ⓞ M7XJ
Features	Alarm history	● (100)	● (100)	● (100)	● (100)	● (100)
	External start	●	●	●	●	●
	Start inhibition	●	●	●	●	●
	Mains failure start			●	●	●
	Start under normative EJP	●	●	●		●
	Pre-heating engine control	●	●	●		●
	Genset contactor activation	●	●	●	●	●
	Mains & Genset contactor activation			●	●	●
	Fuel transfer control	●	●	●		●
	Engine temperature control	●	●	●		●
	Manual override	●	●	●		●
	Programmable alarms	●	●	●		●
	Genset start function in test mode	●	●	●	●	●
	Programmable outputs	●	●	●		●
	Multilingual		●	●	●	●
Special Functions	GPS Positioning		ⓞ	ⓞ		
	Synchronisation		ⓞ	ⓞ		
	Mains synchronization		ⓞ	ⓞ		
	Second Zero elimination		ⓞ	ⓞ		
	RAM7		ⓞ	ⓞ		
	Remote screen		ⓞ	ⓞ		

● Standard ⓞ Optional

ISO 9001
Ctra. Murcia - San Javier, km. 23,6 | 30730 San Javier (Murcia) SPAIN | Tel.: +34 902 19 11 28 / +34 968 19 11 28
Fax: +34 968 19 12 17 | Export Fax +34 968 19 04 20 | E-mail:info@himoinsa.com | www.himoinsa.com
HIMOINSA A YANMAR COMPANY



CONTROL PANELS



AS5


Automatic panel WITHOUT transfer switch and WITHOUT mains control with CEM7 unit. (*) AS5 as optional with CEA7 unit. Automatic panel without transfer switch and WITH mains control.



AS7

Automatic control panel WITHOUT Transfer Switch and WITHOUT mains control with M7X unit.

Digital control unit M7X



CC2

Himoinsa Switching cabinet WITH display.

Digital control unit CEC7



AS5 + CC2

Automatic panel WITH transfer switch and with mains control. The display will be on the genset and on the cabinet.

Digital control unit CEM7+CEC7



AS7 + CC2

Automatic control panel WITH transfer switch and WITH mains control. The display will be on the genset and on the cabinet.

Digital control unit M7X+CEC7



AC5

Automatic mains failure control panel. Wall-mounted cabinet WITH transfer switch and thermal magnetic protection (depending on current and voltage).

Digital control unit CEA7

Electrical system

- Electric control and power panel with measurements devices and control unit (according to necessity and configuration)
- 4-pole thermal magnetic circuit breaker
- Adjustable earth leakage protection
- Battery charger (standard on gensets with automatic control panels)
- Heating resistor (standard on sets with automatic control panels)
- Battery charger alternator with ground connection
- Starter battery/ies installed (cables and bracket included)
- Ground connection electrical installation with connection ready for ground spike (not supplied)
- Battery Switch (Opcional).
- Leakage detector (Opcional).
- Optional Battery (Optima) (Opcional).

2023-JUN.-02 10:59

Ctra. Murcia - San Javier, km. 23,6 | 30730 San Javier (Murcia) SPAIN | Tel.: +34 902 19 11 28 / +34 968 19 11 28
Fax: +34 968 19 12 17 | Export Fax +34 968 19 04 20 | E-mail:info@himoinsa.com | www.himoinsa.com